



Note:

1.Material:

- 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: copper alloy,t=0.20mm
- 1.3 Shell: copper alloy,t=0.25mm

2.Specification:

- 2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.
- 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 100 MΩ Min.
- 2.5 Total mating force: 3.57 Kgf Max.
- 2.6 Total unmating force: 1.0 Kgf Min.
- 2.7 Temperature range: -30°C~80°C

A 01 S B X X X X X XX-835

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

- ① 外壳材质 1: C2680R-H
- ② 外壳电镀 1: NS0u''
- ③ 雾T50u''
- ④ 3: N+Au1u'' (脚)
- ⑤ 4: Au1u''
- ⑥ 端子电镀 01: Au1u''; 02: Au1.5u''; 03: Au3u''
- ⑦ 05: Au5u''; 10: Au10u''; 15: Au15u''; 30: Au30u''
- ⑧ 主体颜色 B: 黑色
- ⑨ 主体材质 1: LCP
- ⑩ 端子材质 4: OS191R-EH

HAOFU ELECTRONCS TECHNOLOGY CO., LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		Micro usb 5P B Type 插板7.2有柱脚长1.1四脚全插		CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE	UP TO 5	±0.2	APPROVAL	SCALE	DATE	
	OTHERWISE	ABOVE 5~30	±0.3			PAGE	1 OF 1
		ABOVE 30	±0.5		2:1		
		ANGLE	±3°				