



Note:
 1. Material:
 1.1 Housing: LCP+G.F, UL94v-0, BLACK
 1.2 Contact: copper alloy, t=0.20mm
 1.3 Shell: StainlessSteel, t=0.25mm
 1.4 COVER: PA9T+G.F, BLACK
 2. Specification:
 2.1 Current rating: 1A Max
 2.2 withstanding woltage: 100V(AC) for 1 min.
 2.3 Contact resistance: 50mΩ Max.
 2.4 Insulation resistance: 100mΩ min.
 2.5 mating force: 3.57 Kgf Max.
 2.6 unmating force: 1.0Kgf Initial, 0.8Kgf after tested.
 2.7 Temperature range: -30° C~80° C

④	COVER	1	PA9T	UL94V-0, BLACK
③	SHELL	1	StainlessSteel	Ni PLATED, T=0.25
②	CONTACT	5	Copper alloy	G/F, T=0.20
①	HOUSING	1	LCP	UL94V-0, BK
ITEM	PART NAME	Q' TY	MATETIALS	REMARK

HAOFU ELECTRONCS TECHNOLOGY CO., LTD		PART NAME	CONNECTOR		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
		PART NO.	MICRO USB AB/F 5P 180度插板 防水		CHECK	G.C.Chen	REV.	A1
		UNIT : mm	TOLERANCE OTHERWISE	UP TO 5 ±0.2 ABOVE 5~30 ±0.3 ABOVE 30 ±0.5 ANGLE ±3°	APPROVAL		DATE	
COPYRIGHT RESERVED,PLEASE DO NOT COPY.					SCALE	2:1	PAGE	1 OF 1