



RECOMMENDED PCB LAYOUT

Tolerance: ±0.05mm

6	防水圈	1	Silicone	
5	固定片	2	C2680 t=0.3	1st: Ni 40u"MIN 2nd: Sn80u"MIN
4	端子	5	C18140 t=0.2	Under plating: Ni plating 50u"MIN Contact area: Au plating 30u"MIN Soldering area : Sn plating 80u"MIN
3	外壳	1	SUS304 t=0.25	Nickel 30u"Min plating all over
2	主体	1	LCP UL 94V-0	BLACK
1	外套	1	PA9T UL 94V-0	BLACK
NO.	PART NAME	QTY.	MATERIAL	REMARK

HAOFU ELECTRONICS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		MICRO USB BF 5P 90SMT 防水 有固定片		CHECK	G.C.Chen	REV.	A1
UNIT :	mm	UP TO 5	±0.2	APPROVAL	SCALE	DATE	PAGE
		ABOVE 5~30	±0.3				
		TOLERANCE OTHERWISE	±0.5	ANGLE	2:1	1 OF 1	
			±3	0°±3'			