



性能:

- 额定电流: 3A
- 额定电压: 30V
- 耐电压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: -55℃~+125℃
- 塑件(材质): PA9T
- 接触点(材质): 磷铜, 镀金5U

Pin数	PART NO.	DIM A	DIM B
2P	BC2P40H80-5U	7.7	5.11
3P	BC3P40H80-5U	11.7	9.11
4P	BC4P40H80-5U	15.7	13.11
5P	BC5P40H80-5U	19.7	17.11
6P	BC6P40H80-5U	23.7	21.11

HADFU ELECTRONICS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		BC6P40H80-5U		CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5 ±0.2	ABOVE 5~30 ±0.3	ANGLE APPROVAL		DATE	26-11-2013
		ABOVE 30 ±0.5	ANGLE ±3°		SCALE	2:1	PAGE