



RECOMMENDED PCB LAYOUT
TOL:(±0.05)

NOTES:

1.Material:

Housing:LCP UL 94V-0,Black

Terminal:Copper Alloy

2.Finish:Plating Gold

3.Specification

Rated Voltage(Max.):30V AC/DC

Dielectric Strength:1KV AC For 1 Minute

Between Adjacent Terminal,No Breakdown

Insulation Resistance:1000 Megohms Min. 500V

DC For 1 Minute Between Adjacent Terminal

Operating Temperature:-20°C-80°C

4.Order information:

BC10P20H260	22.00	18.00	21.40
BC9P20H260	20.00	16.00	19.40
BC8P20H260	18.00	14.00	17.40
BC7P20H260	16.00	12.00	15.40
BC6P20H260	14.00	10.00	13.40
BC5P20H260	12.00	8.00	11.40
BC4P20H260	10.00	6.00	9.40
BC3P20H260	8.00	4.00	7.40
BC2P20H260	6.00	2.00	5.40
Be filled	DIMA	DIMB	DIMC

HAOFU ELECTRONCS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING		Y,C,ZHANG		DWG.No.		SBICL	
PART NO.		BCNP20H260		CHECK		G.C.Chen		REV.		A1	
UNIT :	TOLERANCE OTHERWISE	UP TO 5 ABOVE 5~30 ABOVE 30 ANGLE	±0.2 ±0.3 ±0.5 ±3°	ANGLE	APPROVAL		DATE		22-12-2018		
					SCALE		PAGE		1 OF 1		
mm				0°±3°	2:1		PAGE		1 OF 1		