



性能:

- 额定电流: 3A
- 额定电压: 30V
- 耐电压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: -55℃~+125℃
- 塑件(材质): PA9T
- 接触点(材质): 磷铜, 镀金5U

Pin数	PART NO.	DIM A	DIM B
2P	BC2P40H80-5U	7.7	5.11
3P	BC3P40H80-5U	11.7	9.11
4P	BC4P40H80-5U	15.7	13.11
5P	BC5P40H80-5U	19.7	17.11
6P	BC6P40H80-5U	23.7	21.11

HADFU ELECTRONICS TECHNOLOGY CO.,LTD		PART NAME		CONNECTOR		DRAWING		Y,C,ZHANG		DWG.No.		SBICL	
		PART NO.		BC6P40H80-5U		CHECK		G.C.Chen		REV.		A1	
COPYRIGHT RESERVED,PLEASE DO NOT COPY.		UNIT :		TOLERANCE		ANGLE		APPROVAL		DATE		26-11-2013	
		mm		UP TO 5 ±0.2 ABOVE 5~30 ±0.3 ABOVE 30 ±0.5 ANGLE ±3°		0°±3°		SCALE		PAGE		1 OF 1	