



性能:

- 额定电流: 5.0A
- 额定电压: 30V
- 耐电压: 500V
- 接触电阻: 50mΩ Max
- 绝缘电阻: 500MΩ Min
- 工作温度: -40℃~+85℃
- 塑件(材质): LCP
- 接触点(材质): 磷铜, 触点镀金3U",
- 使用寿命: 5000次以上

HADFU ELECTRONCS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

|              |                        |                       |              |         |           |         |            |
|--------------|------------------------|-----------------------|--------------|---------|-----------|---------|------------|
| PART NAME    |                        | CONNECTOR             |              | DRAWING | Y,C,ZHANG | DWG.No. | SBICL      |
| PART NO.     |                        | BC2P425H74            |              | CHECK   | G.C.Chen  | REV.    | A1         |
| UNIT :<br>mm | TOLERANCE<br>OTHERWISE | UP TO 5<br>ABOVE 5~30 | ±0.2<br>±0.3 | ANGLE   | APPROVAL  | DATE    | 21-07-2014 |
|              |                        | ABOVE 30<br>ANGLE     | ±0.5<br>±3°  | 0°±3°   | SCALE     | PAGE    | 1 OF 1     |