


SYMBOL	REVISION	APPROVAL	DATE

1. ELECTRICAL CHARACTERISTICS:
 - 1-1.RATING: DC 12V 2A
 - 1-2.CONTACT RESISTANCE: 30mΩ MAX(INITAL)
 - 1-3.DIELECTRIC WITHSTANDING VOLTAGE:
500V AC FOR ONE MINUTE
 - 1-4.INSULATION RESISTANCE: 1000MΩ MIN,
MEASURED BY 500V DC



COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR				DRAWING	Y.C,ZHANG	DWG.No.	SBICL
PART NO.		CH01-3PM				CHECK	G.C.Chen	REV.	A1
	UNIT :	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL		DATE	22-02-2017
	mm		ABOVE 5 ~30	±0.3		ABOVE 30	±0.5	SCALE	2:1
			ANGLE	±3°					

PART NAME		CONNECTOR				DRAWING	Y.C,ZHANG	DWG.No.	SBICL
PART NO.		CH01-3PM				CHECK	G.C.Chen	REV.	A1
	UNIT :	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL		DATE	22-02-2017
	mm		ABOVE 5 ~30	±0.3		ABOVE 30	±0.5	SCALE	2:1
			ANGLE	±3°					