



1. Rating:DC30V 0.1A.
2. Circuit:2C-2P.
3. Timing:Non-Shorting
4. Operating Mode:Self-Lock
5. Stroke:Full 2.5mm  
Lock 1.5mm
6. Operating Force:250±100gf
7. Contact Resistance: <100mΩ
8. ELECTRONICS LIFE:shall be operated 10000 CYCLES at  
15~18cycles/min without load .

⑦	底座	PA66	黑色	—
⑥	插片	黄铜/PA66	银色/黑色	镀银
⑤	弹簧	T10A	黑色	发黑处理
④	钩针	碳钢丝	—	—
③	接触片	复银铜	黄色	—
②	按键	POM	白色	—
①	上盖	PA66	灰色	—
	名称 DESCRIPTION	材料 MATERIAL	颜色 COLOR	备注 REMARK

HADFU ELECTRONICS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		PUSH SWITCH		DRAWING		Y,C,ZHANG		DWG.No.		SBICL	
PART NO.		PB22E85		CHECK		G.C.Chen		REV.		A1	
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE		PAGE		1 OF 1	
		ABOVE 5~30	±0.3			SCALE					
		ABOVE 30	±0.5	0°±3'		2:1					