


NOTES:

- 1.ELECTRIC CHARACTERISTICS:
 - 1-1.CONTACT CURRENT RATING: 4A.
 - 1-2.CONTACT VOLTAGE RATING: 20V DC.
 - 1-3.CONTACT RESISTANCE: 30mΩ MAX.;
 - 1-4.DIELECTRIC WITHSTANDING VOLTAGE: 500V AC;
 - 1-5.INSULATION RESISTANCE: 100MΩ MIN.AT DC 500V.
- 2.MECHANICAL CHARACTERISTICS:
 - 2-1.DURABILITY:3000 CYCLES.
 - 2-2.INSERTION AND EXTRACTION FORCE:
 - 2-2.1.INSERTION FORCE: 30N MAX.
 - 2-2.2.EXTRACTION FORCE: 3N MIN.
- 3.ENVIRONMENT CHARACTERISTICS:
 - 3-1.OPERATING TEMPERATURE:-25℃~+85℃.
 - 3-2.HUMIDITY:45~85% RH.

RECOMMENDED PCB LAYOUT
TOP VIEW



4	底座	1	PA66	BLACK
3	开关静片	1	黄铜 T=0.4mm	Ag PLATED
2	开关弹片	1	磷铜 T=0.3mm	Ag PLATED
1	电极中心引脚	1	黄铜 T=0.5mm	Ag PLATED
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR

HAOFU ELECTRONCS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME	DC POWER JACK		DRAWING	G.C.Chen	DG.No.	
PART NO.	DC-080		CHECK	G.C.Chen	REV.	A
UNIT :	TOLERANCE	UP TO 5	ANGLE	APPROVAL	DATE	
mm	OTHERWISE	ABOVE 5~30	0°±3'	SCALE	PAGE	1 OF 1
		±0.2		2:1		
		±0.3				
		±0.5				
		±3'				