


**SPECIFICATIONS:**

1. TEMPERATURE RANGE:  $-30 \sim 70^{\circ}$
2. RATED VOLTAGE/CURRENT: DC30V /5A
3. CONTACT RESISTANCE:  $\leq 0.03 \Omega$
4. INSULATION RESISTANCE:  $\geq 100M \Omega$  DC250V
5. WITHSTANDING VOLTAGE: AC500V(50Hz)/min
6. INSERTION FORCE: 3~20N
7. DURABILITY CYCLES: 5000CYCLES

ELECTRICAL CIRCUIT



NO.	DESCRIPTION	QTY	MATERIAL	FINISH
4	INSULATION	1	PA66	BLACK
3	PIN	1	BRASS	D. CuSn
2	TERMINAL	1	PHOSPHOROUS BRONZE T=0.35	D. CuSn
1	BODY	1	COPPER ALLOY	D. CuSn

HAOFU ELECTRONCS TECHNOLOGY CO.,LTD

PART NAME		DC POWER JACK		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		DC-099		CHECK	G.C.Chen	REV.	A1
UNIT :	TOLERANCE OTHERWISE	UP TO 5	$\pm 0.2$	APPROVAL	SCALE	DATE	PAGE
		ABOVE 5 ~30	$\pm 0.3$			1 OF 1	
mm		ABOVE 30	$\pm 0.5$		2:1		
		ANGLE	$\pm 3'$				

COPYRIGHT RESERVED,PLEASE DO NOT COPY.