



备注:

1. 电气性能:

- 1-1. 额定电流: 2.0A
- 1-2. 额定电压: 12V DC
- 1-3. 耐电压: 500V AC, 1min
- 1-4. 接触电阻: 30mΩ
- 1-5. 绝缘电阻: 100MΩ

2. 工作温度: -20℃~+60℃

3. 环境管控:

- 3-1. 禁止使用含有ROHS所限制的物质。
- 3-2. 对应第三方测试机构出具的ICP-AES数据和不可测定物质的成分表, 在一年有效期内。

3	HOUSING	1 PCS	PBT+15%GF	BLACK
2	PIN(2#)	1 PCS	PHOSPHOR BRONZE T=0.25	Sn-Plating
1	PIN(1#)	1 PCS	C2680	Sn-Plating
ITFM	COMPONENT	0' TY		FINISH

HAOFU ELECTRONCS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		DC POWER JACK		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		DC-0116		CHECK	G.C.Chen	REV.	A1
UNIT :	TOLERANCE	UP TO 5	±0.2	APPROVAL	DATE		SCALE
	OTHERWISE	ABOVE 5 ~30	±0.3		PAGE		
mm		ANGLE	±0.5	SCALE	2:1	PAGE	1 OF 1
		ANGLE	±3'				