


- SPECIFICATION**
- 1.Rating : DC 20V 15A;
 - 2.Contact resistance: $\leq 30\text{m}\Omega$;
 - 3.Insulation resistance: $\geq 100\text{M}\Omega$ (DC250V);
 - 4.Withstand voltage: 500VAC ;
 - 5.Insertion and extraction force: 3-20N;
 - 6.life test: 5,000 cycles.



⑥	Washer	1	Spring steel	Sn-Plating
⑤	Nut	1	H59 BRASS	Ag-Plating
④	Tip spring	1	Bronze C5191 t=0.2	Ag-Plating
③	PIN	1	H59 BRASS	Ag-Plating
②	Housing	1	PBT	Black
①	Bushing	1	H59 BRASS	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

HAOFU ELECTRONCS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		DC POWER JACK		DRAWING	G.C.Chen	DWG.No.	
PART NO.		DC-199A		CHECK	G.C.Chen	REV.	A
UNIT : mm	TOLERANCE OTHERWISE	UP TO 5	±0.2	ANGLE	APPROVAL	DATE	
		ABOVE 5~30	±0.3				
		ABOVE 30	±0.5	SCALE	2:1	PAGE	1 OF 1
		ANGLE	±3'				