



材料:

- A 基座: 进口增强尼龙 (黑色)
- B 嵌件: 进口磷青铜 (镀银与银白色)
- C 接触弹簧: 进口磷青铜 (镀银与银白色)
- D 盖板: 进口增强尼龙 (整体清洗与黑色)
- E 按钮: 进口增强尼龙 (黑色)
- F 贴片按钮: 不锈钢 (原色)

主要技术规格:

1. 额定值: 0.1A MAX
2. 接触电阻:  $\leq 200m\Omega$
3. 操作力:  $500gf \pm 30gf$
4. 行程:  $1.0 \pm 0.3mm$
5. 绝缘电阻:  $\geq 100M\Omega$
6. 耐压强度: AC250V 50HZ/ 1Min.
7. 寿命: 5万Cycles Min
8. 额定电压: DC 12V

HAOFU ELECTRONICS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		DETECTION SWITCH		DRAWING		Y,C,ZHANG	DWG.No.	SBICL
PART NO.		TC-1626DA-01W		CHECK		G.C.Chen	REV.	A1
	UNIT :	TOLERANCE	UP TO 5	$\pm 0.2$	ANGLE	APPROVAL	DATE	PAGE
	mm		OTHERWISE	ABOVE 5~30				
			ABOVE 30	$\pm 0.5$		SCALE	2:1	1 OF 1