


P.C.B LAYOUT
BOTTOM VIEW

注“*”表示关键尺寸(8个)



SCHEMATIC

- 1、开关动作力: 100 ± 30 gf.cm
- 2、回返力: 30gf.cm Min
- 3、额定值: DC30V 0.1A
- 4、接触电阻: $200\text{m}\Omega$ Max
- 5、绝缘电阻: $\geq 100\text{M}\Omega$ (MinDC250V)
- 6、耐压: 250V AC(50HZ或60HZ)/1min
- 7、机械寿命: 50000 Min

NO.	PARTS	MATERIALS	QTY	FINISH
6	TERMINAL	BRASS	1	Ag PLATED
5	CASE	PA66	1	BLACK
4	SPRING	SUS	1	NATURAL
3	CONTACT	PBS STRIP	1	Ag CLAD
2	BUTTON	PA66	1	YELLOW
1	COVER	PA66	1	BLACK

HAOFU ELECTRONCS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		DETECTION SWITCH		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		TC-0036Y		CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE	UP TO 5	± 0.2	APPROVAL	SCALE	DATE	
	OTHERWISE	ABOVE 5 ~ 30	± 0.3			ANGLE	2:1
		ABOVE 30	± 0.5				
		ANGLE	$\pm 3'$				