



■ 电路图

	①	②	③	④	⑤	⑥
F1	○			○		
F2	●	●				
F3	○					○
F4	○				○	
F5	○	○				

材料:

- A按钮: PA46(黑色)
- B梅花护套: LCP(灰黑色)
- C盖板: SUS(清洗与白色)
- D底座: PA46(黑色)
- E接触垫片: 复银铜(银白色镶银)
- F弹片: 复银不锈钢(银白色镶银)
- G嵌件: 磷铜(镀银与银白色)

主要技术规格:

1. 额定值: 0.1A MAX
2. 接触电阻: $\leq 80m\Omega$
3. 操作力: $200gf \pm 50gf$
4. 行程: $0.20 \pm 0.05mm$
5. 绝缘电阻: $\geq 100M\Omega min(DC100V)$
6. 耐压强度: AC250V 50HZ/ 1Min.
7. 寿命: 5万Cycles Min
8. 额定电压: DC 12V

HAOFU ELECTRONICS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		MULTI FUNCTION SWITCH		DRAWING	Y,C,ZHANG	DWG.No.	SBICL
PART NO.		MT-1504SA-06		CHECK	G.C.Chen	REV.	A1
UNIT : mm	TOLERANCE	UP TO 5	± 0.2	APPROVAL	SCALE	DATE	PAGE
	OTHERWISE	ABOVE 5~30	± 0.3			ANGLE	
		ABOVE 30	± 0.5		2:1		
		ANGLE	$\pm 3'$				