



材料:  
 A底座/基座: LCP(黑色)  
 B嵌件: C5191R (整体镀银与银白色)  
 C手柄: 进口增强尼龙  
 D簧片: QBe2 (接触单面镀银与接触面银白色)  
 E盖板: C5191R (整体镀银)  
 F弹条: SUS301 (整体清洗与银白色)

主要技术规格:

1. 额定值: 50mA MAX
2. 接触电阻:  $\leq 70m\Omega$
3. 操作力:  $150gf \pm 50gf$
4. 行程:  $1.2 \pm 0.2mm$
5. 绝缘电阻:  $\geq 100M\Omega$
6. 耐压强度: AC250V 50HZ/ 1Min.
7. 寿命: 1万Cycles Min
8. 额定电压: DC 12V

HAOFU ELECTRONCS TECHNOLOGY CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING		Y,C,ZHANG	DWG.No.	SBICL
PART NO.		MSK-1293S		CHECK		G.C.Chen	REV.	A1
UNIT :	TOLERANCE OTHERWISE	UP TO 5	$\pm 0.2$	ANGLE	APPROVAL	DATE	PAGE	14-03-2013
		ABOVE 5~30	$\pm 0.3$					
mm		ABOVE 30	$\pm 0.5$	$0^\circ \pm 3'$	SCALE	2:1	1 OF 1	